

---

## KEMPPi Minarc 150 elektrodesvejser - Specifikationer

---

Connection voltage 1 ~ phase 50/60 Hz	230 V ± 15 %
Rated power at max. current	
35 % ED MMA	140 A/7.5 kVA
100 % ED MMA	100 A/5.1 kVA
35 % ED TIG	150 A/5.0 kVA
100 % ED TIG	110 A/3.3 kVA
Supply current	
35 % ED I <sub>1max</sub>	27 A
100 % ED I <sub>1eff</sub>	16 A
Connection cable	H07RN-F, 3G2.5 (2.5 mm <sup>2</sup> , 3 m)
Fuse (delayed)	16 A
Welding range	
MMA	10 A/20.5 V – 140 A/25.6 V
TIG	5 A/10 V – 150 A/16 V
Welding current control	Stepless
Open circuit voltage	85 V, (VRD 30 V)
Idle power	<10 W
Power factor at 100% ED	0,60
Efficiency at 100% ED	80 %
Stick electrodes	1.5–3.25 mm Ø
External dimensions LxWxH	320x123x265 mm
Weight without connection cable	4.0 kg
Weight with connection cable	4.6 kg
Temperature class	B (130° C)
Operating temperature range	-20...+40° C
Storage temperature range	-40...+60° C
Degree of protection	IP23S
EMC class	A
Norms	EN/IEC 60974-1 EN/IEC 60974-10

Modelår

2016

Der tages forbehold for trykfejl og ændringer i specifikationer uden forudgående varsel.

**Leje-PLADSEN.DK**

Trailer- og maskinudlejning